

# AMMONIA

<b>AMMONIA STANDARD, 0.2 ppm as N</b>	<b>A-37J</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 1.0 ppm as N</b>	<b>A-37C</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 2.0 ppm as N</b>	<b>A-37G</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 3.0 ppm as N</b>	<b>A-37M</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 5.0 ppm as N</b>	<b>A-37F</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 10.0 ppm as N</b>	<b>A-37B</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 20.0 ppm as N</b>	<b>A-37H</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 30.0 ppm as N</b>	<b>A-37K</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 50.0 ppm as N</b>	<b>A-37L</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>AMMONIA STANDARD, 100 ppm as N</b>	<b>A-37A</b>	500 ml liter	<b>15.60</b> <b>23.40</b>
<b>AMMONIA STANDARD, 1000 ppm as N</b>	<b>A-37</b>	500 ml liter	<b>17.50</b> <b>26.00</b>
<b>AMMONIA CALIBRATION 6-pack</b> Two 500 ml bottles each of the following <b>Ammonia Standards: 0.2 ppm, 2.0 ppm, and 20 ppm.</b> (No substitutions, please)	<b>NH3-SET</b>	6 x 500 ml	<b>70.20</b>
<b>Thermo Scientific Orion AMMONIA ISA BUFFER HM</b> (For use with Ammonia ISE)	<b>O-951211</b>	475 ml	<b>77.40</b>
<b>Thermo Scientific Orion AMMONIA STANDARD, 100 ppm as N</b>	<b>O-951207</b>	475 ml	<b>52.20</b>
<b>Thermo Scientific Orion AMMONIA STANDARD, 1000 ppm as N</b>	<b>O-951007</b>	475 ml	<b>61.20</b>



## BOD

### BOD STANDARD, 198 PPM (GLUCOSE-GLUTAMIC ACID STANDARD)

Made according to Standard Methods specifications, autoclaved and vacuum-sealed in 50 ml vials, offering many advantages over ampules. Each vial contains enough standard for 8 tests.

- ✓ No ampules to break. Just unscrew the cap.
- ✓ No multiple dilutions required. Use 6 ml per 300 ml BOD bottle.
- ✓ Minimizes waste. Use what you need, refrigerate the remainder for future use.
- ✓ Shelf-life is 12 months for unopened bottles and 2 months for opened bottles, as long as no contamination has occurred.
- ✓ Lower cost... less than \$0.60 per test.



Size	NCL #	Price/ea
50 ml	B-12D	4.50
12 x 50 ml		45.00

## CHLORIDE

<b>CHLORIDE STANDARD, 100 ppm as Cl</b>	<b>C-8C</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>CHLORIDE STANDARD, 1000 ppm as Cl</b>	<b>C-8D</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>CHLORIDE STANDARD, 10,000 ppm as Cl</b>	<b>C-8E</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>Thermo Scientific Orion CHLORIDE STANDARD 100 ppm as Cl</b>	<b>O-941707</b>	475 ml	<b>56.70</b>
<b>Thermo Scientific Orion CHLORIDE STANDARD 1000 ppm as Cl</b>	<b>O-941708</b>	475 ml	<b>56.70</b>

## CHLORINE

<b>NCL CHLORINE STANDARD, 100 ppm as Cl</b> (For use with Chlorine ISE)	<b>C-9A</b>	500 ml liter	<b>22.90</b> <b>34.30</b>
<b>Thermo Scientific Orion CHLORINE STANDARD, 100 ppm as Cl</b> (For use with Chlorine ISE)	<b>O-977007</b>	475 ml	<b>69.30</b>
<b>CHLORINE STANDARD, 1000 ppm as Cl</b> for use in DPD colorimetric test procedures (Potassium Permanganate, 0.891 g/l)	<b>C-9B</b>	pint	<b>22.90</b>



## COD

<b>COD STANDARD, 500 ppm</b>	<b>C-50D</b>	500 ml	<b>18.70</b>
<b>COD STANDARD, 1000 ppm</b>	<b>C-99D</b>	500 ml	<b>18.70</b>
<b>COD STANDARD, 4000 ppm</b>	<b>C-49D</b>	500 ml	<b>24.95</b>

## CONDUCTIVITY

<b>CONDUCTIVITY STANDARD</b> 14.9 micromhos/cm (0.0001 M KCl)	<b>C-37G</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 74 micromhos/cm (0.0005 M KCl)	<b>C-37H</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 147 micromhos/cm (0.001 M KCl)	<b>C-37J</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 718 micromhos/cm (0.005 M KCl)	<b>C-37K</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 1413 micromhos/cm (0.01 M KCl)	<b>C-37L</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 2767 micromhos/cm (0.02 M KCl)	<b>C-37M</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 6668 micromhos/cm (0.05 M KCl)	<b>C-37P</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>CONDUCTIVITY STANDARD</b> 12900 micromhos/cm (0.1 M KCl)	<b>C-37Q</b>	500 ml liter	<b>14.55</b> <b>21.85</b>

### SINGLE-USE CONDUCTIVITY CALIBRATION STANDARDS

Extra-large opening (1<sup>3</sup>/<sub>4</sub>" diameter) accommodates virtually all conductivity probes. The solution is compatible with all conductivity meters and probes. Supplied as a pack of 6 x 100 ml standards traceable to NIST.



Micromhos	NCL #	Price/pk
10	<b>CC-175</b>	<b>25.30</b>
100	<b>CC-176</b>	<b>25.30</b>
1413	<b>CC-174</b>	<b>25.30</b>
10,000	<b>CC-178</b>	<b>25.30</b>

## FLUORIDE

<b>FLUORIDE STANDARD, 0.20 mg/l</b>	<b>F-34A</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 0.50 mg/l</b>	<b>F-34E</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 0.75 mg/l</b>	<b>F-35B</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 1.00 mg/l</b>	<b>F-36</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 1.20 mg/l</b>	<b>F-37</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 1.25 mg/l</b>	<b>F-37A</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 1.40 mg/l</b>	<b>F-37B</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 1.50 mg/l</b>	<b>F-37C</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 1.75 mg/l</b>	<b>F-37D</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 2.00 mg/l</b>	<b>F-37E</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 5.0 ppm</b>	<b>F-39L</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>FLUORIDE STANDARD, 10.0 ppm</b>	<b>F-39A</b>	500 ml liter 3.8 liter	<b>13.50</b> <b>20.30</b> <b>50.70</b>
<b>FLUORIDE STANDARD, 20 ppm</b>	<b>F-39B</b>	500 ml liter 3.8 liter	<b>14.05</b> <b>21.30</b> <b>52.00</b>



# FLUORIDE

<b>FLUORIDE STANDARD, 100 ppm</b>	<b>F-39</b>	500 ml liter	<b>18.70</b> <b>28.10</b>
<b>FLUORIDE STANDARD, 1000 ppm</b>	<b>F-38</b>	500 ml liter	<b>21.85</b> <b>32.75</b>
<b>FLUORIDE STANDARD, 1 ppm with TISAB II</b>	<b>F-39M</b>	500 ml liter 3.8 liter	<b>24.95</b> <b>37.45</b> <b>93.60</b>
<b>FLUORIDE STANDARD, 2 ppm with TISAB II</b>	<b>F-39P</b>	500 ml liter 3.8 liter	<b>24.95</b> <b>37.45</b> <b>93.60</b>
<b>FLUORIDE STANDARD, 10 ppm with TISAB II</b>	<b>F-39Q</b>	500 ml liter 3.8 liter	<b>24.95</b> <b>37.45</b> <b>93.60</b>
<b>Thermo Scientific Orion FLUORIDE STANDARD 1 ppm with TISAB II</b>	<b>O-040906</b>	475 ml	<b>65.70</b>
<b>Thermo Scientific Orion FLUORIDE STANDARD 2 ppm with TISAB II</b>	<b>O-040907</b>	475 ml	<b>65.70</b>
<b>Thermo Scientific Orion FLUORIDE STANDARD 10 ppm with TISAB II</b>	<b>O-040908</b>	475 ml	<b>65.70</b>
<b>FLUORIDE STANDARD #1 "100 ppm as F"</b> (For Metal finishing industry-This standard is a 1:1 volumetric mixture of 100 ppm Fluoride standard and Sodium Acetate Buffer, pH 5.4)	<b>F-39X</b>	liter	<b>31.20</b>
<b>FLUORIDE STANDARD #2 "1000 ppm as F"</b> (For Metal finishing industry-This standard is a 1:1 volumetric mixture of 1000 ppm Fluoride standard and Sodium Acetate Buffer, pH 5.4)	<b>F-39Y</b>	liter	<b>31.20</b>

## HARDNESS

<b>HARDNESS STANDARD</b> (100 ppm as CaCO <sub>3</sub> )	<b>H-6</b>	500 ml liter	<b>24.95</b> <b>37.45</b>
<b>HARDNESS STANDARD</b> (1000 ppm as CaCO <sub>3</sub> )	<b>H-6A</b>	500 ml liter	<b>24.95</b> <b>37.45</b>

## NITRATE

<b>NITRATE STANDARD, 1.0 ppm as N</b>	<b>N-26B</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>NITRATE STANDARD, 2.0 ppm as N</b>	<b>N-26C</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>NITRATE STANDARD, 10 ppm as N</b>	<b>N-26A</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>NITRATE STANDARD, 20 ppm as N</b>	<b>N-26D</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>NITRATE STANDARD, 100 ppm as N</b>	<b>N-27</b>	500 ml liter	<b>16.65</b> <b>24.95</b>
<b>NITRATE STANDARD, 1000 ppm as N</b>	<b>N-27A</b>	500 ml liter	<b>16.65</b> <b>24.95</b>
<b>Thermo Scientific Orion NITRATE STANDARD, 100 ppm as N</b>	<b>O-930707</b>	475 ml	<b>70.20</b>
<b>Thermo Scientific Orion NITRATE STANDARD, 1000 ppm as N</b>	<b>O-920707</b>	475 ml	<b>70.20</b>

## NITRITE

<b>NITRITE STANDARD, (100 ppm as N)</b>	<b>N-28</b>	500 ml	<b>37.45</b>
---	-------------	--------	--------------



# ORP

<b>LIGHT'S SOLUTION (ORP STANDARD)</b> HM	<b>L-15</b>	pint	<b>33.30</b>
<b>ZOBELL'S SOLUTION (ORP STANDARD)</b>	<b>Z-65</b>	pint	<b>27.55</b>

## 420mv ORP STANDARD FOR O-9678BN

Size	NCL #	Price
475 ml	<b>O-967901</b>	<b>50.40/ea</b>
5 x 2 oz	<b>O-967961</b>	<b>72.00/pk</b>



# pH

<b>BUFFER SOLUTION, pH=2.00±0.02</b> (pH standardization buffer)	<b>B-42</b>	500 ml liter 3.8 liter	<b>12.45</b> <b>18.70</b> <b>46.80</b>
<b>BUFFER SOLUTION, pH=4.00±0.02</b> (pH standardization buffer) Color coded red	<b>B-44</b>	500 ml 6 x 500 ml liter 6 x 1 liter 3.8 liter 20 liter	<b>8.30</b> <b>37.45</b> <b>12.50</b> <b>56.15</b> <b>29.10</b> <b>99.85</b>
<b>BUFFER SOLUTION, COLORLESS, pH 4.00</b> (pH=4.00±0.02 - Colorless pH standardization buffer)	<b>B-44CL</b>	500 ml liter 3.8 liter 20 liter	<b>9.15</b> <b>13.75</b> <b>32.00</b> <b>109.80</b>
<b>pH 4.00 Buffer with 0.1 M NaCl</b> (For inner-body check on Orion Ammonia probe)	<b>B-44A</b>	500 ml	<b>24.95</b>
<b>BUFFER SOLUTION, pH=5.00±0.02</b> (pH standardization buffer)	<b>B-45</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>BUFFER SOLUTION, pH=6.00±0.02</b> (pH standardization buffer)	<b>B-46</b>	500 ml liter 3.8 liter 20 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b> <b>140.40</b>
<b>BUFFER SOLUTION, pH=6.87±0.02</b> (pH standardization buffer) Color coded green	<b>B-46D</b>	3.8 liter	<b>46.80</b>
<b>BUFFER SOLUTION, pH=7.00±0.02</b> (pH standardization buffer) Color coded yellow	<b>B-47</b>	500 ml 6 x 500 ml liter 6 x 1 liter 3.8 liter 20 liter	<b>8.30</b> <b>37.45</b> <b>12.50</b> <b>56.15</b> <b>29.10</b> <b>99.85</b>
<b>BUFFER SOLUTION, COLORLESS, pH 7.00</b> (pH=7.00±0.02 - Colorless pH standardization buffer)	<b>B-47CL</b>	500 ml liter 3.8 liter 20 liter	<b>9.15</b> <b>13.75</b> <b>32.00</b> <b>109.80</b>



# pH

<b>pH 7.00 Buffer with 0.1 M NaCl</b> (For inner-body check on Orion Ammonia probe)	<b>B-47A</b>	500 ml	<b>24.95</b>
<b>BUFFER SOLUTION, pH=8.00±0.02</b> (pH standardization buffer)	<b>B-48</b>	500 ml liter 3.8 liter 20 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b> <b>140.40</b>
<b>BUFFER SOLUTION, pH=9.00±0.02</b> (pH standardization buffer)	<b>B-49</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>BUFFER SOLUTION, pH=10.00±0.02</b> (pH standardization buffer) Color coded blue	<b>B-50</b>	500 ml 6 x 500 ml liter 6 x 1 liter 3.8 liter 20 liter	<b>8.30</b> <b>37.45</b> <b>12.50</b> <b>56.15</b> <b>29.10</b> <b>99.85</b>
<b>BUFFER SOLUTION, COLORLESS, pH 10.00</b> (pH=10.00±0.02 - Colorless pH standardization buffer)	<b>B-50CL</b>	500 ml liter 3.8 liter 20 liter	<b>9.15</b> <b>13.75</b> <b>32.00</b> <b>109.80</b>
<b>BUFFER SOLUTION, pH=12.45</b>	<b>B-52C</b>	500 ml liter 3.8 liter	<b>12.50</b> <b>18.70</b> <b>46.80</b>
<b>BOD NUTRIENT SET (contains one 500 ml each of C-5, F-10, M-10 &amp; P-30)</b>	<b>B-99</b>	4 x 500 ml	<b>35.00</b>
<b>BUFFER CALIBRATION 6-pack</b> Two 500 ml bottles each of the following pH CALIBRATION BUFFERS: 4.00, 7.00, and 10.00 (No substitutions, please.)	<b>BUF-SET</b>	6 x 500 ml	<b>43.70</b>
<b>pH ELECTRODE PACK</b> Contains one 500 ml bottle of each pH 4, pH 7, and pH 10 buffers plus one 500 ml bottle of electrode storage solution	<b>BUF-KIT</b>	4 X 500 ml	<b>28.00</b>



# pH BUFFER CAPSULES & PACKETS

## CHEMVELOPES

For those of you who like to make up your own buffers. Contents of each envelope are dissolved in 500 ml of distilled water. Five envelopes per pack.

pH	NCL #	Price/pk
4	<b>BM-4</b>	<b>9.00</b>
6	<b>BM-6</b>	<b>9.00</b>
7	<b>BM-7</b>	<b>9.00</b>
10	<b>BM-10</b>	<b>9.00</b>



## THERMO SCIENTIFIC ORION BUFFER PACKETS

Sealed buffer packets, ideal for field calibration of pH meters. Each packet is color-coded and suitable for one pH calibration. Sold in packs of 25 for each pH value. Traceable to NIST.



pH	NCL #	Price/pk
4	<b>O-910425</b>	<b>40.50</b>
7	<b>O-910725</b>	<b>40.50</b>
10	<b>O-911025</b>	<b>40.50</b>
(Rinse Solution)	<b>O-911125</b>	<b>40.50</b>

## BUFFER CAPSULES

Each capsule makes 100 ml of the indicated buffer when mixed with 100 ml of distilled water. Sold in cases of 5 vials; each vial contains 10 capsules.

pH	NCL #	Price/pk
4	<b>BM-24</b>	<b>32.00</b>
7	<b>BM-27</b>	<b>32.00</b>
10	<b>BM-30</b>	<b>32.00</b>



## HACH BUFFER POWDER PILLOWS

Single-use powder pillows for 50 ml sample. Packs of 50 pillows.



pH	NCL #	Price/pk
4	<b>H-22269-66</b>	<b>18.10</b>
7	<b>H-22270-66</b>	<b>18.10</b>
10	<b>H-22271-66</b>	<b>18.10</b>



# pH



## ISA BUFFERS FOR pH

The performance of a pH probe is judged by the time it takes to get a stable reading in pH buffers, NOT IN SAMPLES. You should get a stable reading in a buffer within one minute or less. Clean water samples, such as drinking water and final effluent may take a lot longer (up to 10 minutes) to get a stable reading. The worst case is deionized water, which may take up to ONE HOUR to get a stable reading, due to the low ionic content. Thermo Scientific Orion now offers a series of ISA (Ionic Strength Adjustment) Buffers for pH, which work in a similar fashion to ISA Buffers for other tests, such as Ammonia and Fluoride.



Our tests show that the time for deionized water was reduced from 55 minutes to 6 minutes, and drinking water time was reduced from 8 minutes to 2 minutes. Be sure to check with your State Regulators to see if this system is acceptable.

O-700001 includes: four 475 ml bottles of Buffer A (pH 6.97), two 475 ml bottles of Buffer B (pH 4.10), two 50 ml bottles of pH ISA Buffer, syringe, and instructions.

Description	NCL #	Price
As described	<b>O-700001</b>	<b>208.80</b>
four 475 ml bottles Buffer A (pH 6.97)	<b>O-700702</b>	<b>205.20</b>
four 475 ml bottles Buffer B (pH 4.10)	<b>O-700402</b>	<b>208.80</b>
four 475 ml bottles Buffer C (pH 9.15)	<b>O-700902</b>	<b>208.80</b>
five 2 oz bottles pH ISA Buffer, syringe	<b>O-700003</b>	<b>133.20</b>

## PHOSPHATE

<b>PHOSPHATE STANDARD, 1 ppm as P</b> (1.00 ml = 1 µg P)	<b>P-35F</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>PHOSPHATE STANDARD, 5 ppm as P</b> (1.00 ml = 5 µg P)	<b>P-35A</b>	500 ml liter	<b>12.50</b> <b>18.70</b>
<b>PHOSPHATE STANDARD, 50 ppm as P</b> (1.00 ml = 50 µg P)	<b>P-35</b>	500 ml liter	<b>14.55</b> <b>21.85</b>
<b>PHOSPHATE STANDARD, 1000 ppm</b>	<b>P-34</b>	500 ml liter	<b>18.70</b> <b>28.10</b>

# QA/QC

Laboratory QA/QC Standards are available for the following parameters:

- Ammonia nitrogen
- BOD
- cBOD
- Chloride
- Chlorine (Amperometric Method)
- Chlorine (DPD Method)
- Chlorine (ISE Method)
- COD
- Conductivity
- Fluoride
- Hardness (as CaCO<sub>3</sub>)
- Iron
- Nitrate
- Nitrite
- P-Alkalinity
- pH
- Phosphate (as P)
- TDS
- TKN
- TSS



These standards are suitable for your internal QA/QC program. They are not meant to take the place of your annual standards for certification or registration, which you must obtain from an EPA-designated source.

Standards are available for each analyte individually, so you can purchase only the ones you need. Approximate range and dilution directions are given on each vial. True values are enclosed in a separate envelope with your order, along with a postcard for you to report your results to us, if you choose to do so. Return of the postcard is entirely optional, and all results are strictly confidential. We use this data to establish acceptable ranges for future programs.

The price for these standards is \$15.00 per bottle. Those who return the postcard with their results will receive a discount of \$5.00 per bottle on their next QA/QC order.



# SODIUM

Concentration	Manufactured by	NCL #	Price
1000 ppm as Na	Thermo Scientific Orion	<b>O-841108</b>	<b>57.60/475 ml</b>
1000 ppm as Na	NCL	<b>S-36B</b>	<b>16.65/500 ml</b>

# TURBIDITY

NTU	Size	NCL #	Price
0.0	125 ml	NTU-0-125	<b>20.50</b>
	250 ml	NTU-0-250	<b>26.30</b>
	500 ml	NTU-0-500	<b>38.20</b>
	Liter	NTU-0-Liter	<b>50.10</b>
	Gallon	NTU-0-3.8	<b>135.20</b>
0.1	125 ml	NTU-X1-125	<b>44.20</b>
	250 ml	NTU-X1-250	<b>56.80</b>
	Liter	NTU-X1-Liter	<b>90.60</b>
	Gallon	NTU-X1-3.8	<b>294.60</b>
0.5	125 ml	NTU-X5-125	<b>44.20</b>
	250 ml	NTU-X5-250	<b>56.80</b>
	500 ml	NTU-X5-500	<b>73.60</b>
	Liter	NTU-X5-Liter	<b>90.60</b>
	Gallon	NTU-X5-3.8	<b>294.60</b>
1.0	125 ml	NTU-1-125	<b>44.20</b>
	250 ml	NTU-1-250	<b>56.80</b>
	Liter	NTU-1-Liter	<b>90.60</b>
	Gallon	NTU-1-3.8	<b>294.60</b>
4.0	125 ml	NTU-4-125	<b>48.30</b>
	250 ml	NTU-4-250	<b>62.20</b>
	Liter	NTU-4-Liter	<b>99.30</b>
	Gallon	NTU-4-3.8	<b>303.40</b>
	10	125 ml	NTU-10-125
250 ml		NTU-10-250	<b>62.20</b>
500 ml		NTU-10-500	<b>80.80</b>
Liter		NTU-10-Liter	<b>99.30</b>
Gallon		NTU-10-3.8	<b>303.40</b>
20	125 ml	NTU-20-125	<b>48.30</b>
	250 ml	NTU-20-250	<b>62.20</b>
	500 ml	NTU-20-500	<b>80.80</b>
	Liter	NTU-20-Liter	<b>99.30</b>
	Gallon	NTU-20-3.8	<b>303.40</b>
40	125 ml	NTU-40-125	<b>48.30</b>
	250 ml	NTU-40-250	<b>62.20</b>
	500 ml	NTU-40-500	<b>80.80</b>
	Liter	NTU-40-Liter	<b>99.30</b>
	Gallon	NTU-40-3.8	<b>303.40</b>